



SCALANCE X101-1, IE Media converter unmanaged 1x 10/100 Mbit/s RJ45 port, 1x 100 Mbit/s Multimode BFOC, LED diagnostics, error signaling Contact with Set pushbutton Redundant power supply, PROFINET-compliant securing collars, Manual available as a download available

transfer rate	
transfer rate	100 Mbit/s
Interfaces	
number of electrical/optical connections / for network components or terminal equipment / maximum	2
number of electrical connections	
• for network components or terminal equipment	1
• for signaling contact	1
• for power supply	1
• for redundant voltage supply	1
type of electrical connection	
• for network components or terminal equipment	RJ45 port
• for signaling contact	2-pole terminal block
• for power supply	4-pole terminal block
number of optical interfaces	
• for fiber optic cable / at 100 Mbit/s	1
design of the optical interface	
• for fiber optic cable / at 100 Mbit/s	BFOC-Port (Multimode up to 5 km)
connectable optical power relative to 1 mW	
• of the transmitter output / minimum	-19 dB
• of the transmitter output / maximum	-14 dB
• of the receiver input / maximum	-14 dB
optical sensitivity relating to 1 mW / of the receiver input / minimum	-31 dB
attenuation factor / of the FOC transmission link / minimum necessary	0 dB
range / at the optical interface / depending on the optical fiber used	0 ... 5 km
signal inputs/outputs	
operating voltage / of the signaling contacts	
• at DC / rated value	24 V
operational current / of the signaling contacts	
• at DC / maximum	0.1 A
supply voltage, current consumption, power loss	
supply voltage	
• external	24 V
• external	18 ... 32 V
type of voltage / of the supply voltage	DC
product component / fusing at power supply input	Yes
fuse protection type / at input for supply voltage	0.5 A / 60 V

consumed current	
<ul style="list-style-type: none"> <li>● maximum</li> </ul>	0.12 A
power loss [W]	
<ul style="list-style-type: none"> <li>● at DC / at 24 V</li> </ul>	3 W
<b>ambient conditions</b>	
ambient temperature	
<ul style="list-style-type: none"> <li>● during operation</li> <li>● during storage</li> <li>● during transport</li> </ul>	-10 ... +60 °C -40 ... +80 °C -40 ... +80 °C
relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP30
<b>design, dimensions and weights</b>	
design	Compact
width	40 mm
height	125 mm
depth	124 mm
net weight	0.55 kg
fastening method	
<ul style="list-style-type: none"> <li>● 35 mm top hat DIN rail mounting</li> <li>● S7-300 rail mounting</li> <li>● wall mounting</li> </ul>	Yes Yes Yes
<b>product functions / redundancy</b>	
product function	
<ul style="list-style-type: none"> <li>● Parallel Redundancy Protocol (PRP)/operation in the PRP-network</li> <li>● Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)</li> </ul>	No No
<b>standards, specifications, approvals</b>	
standard	
<ul style="list-style-type: none"> <li>● for FM</li> <li>● for safety / from CSA and UL</li> <li>● for emitted interference</li> <li>● for interference immunity</li> </ul>	FM3611: Class 1, Divison 2, Group A, B, C, D / T..., Class 1, Zone 2, Group IIC, T.. UL 60950-1, CSA C22.2 No. 60950-1 EN 61000-6-3 EN 61000-6-4:2001
certificate of suitability	EN 61000-6-2:2001, EN 61000-6-4:2001
<ul style="list-style-type: none"> <li>● CE marking</li> <li>● C-Tick</li> <li>● KC approval</li> </ul>	Yes Yes Yes
Marine classification association	
<ul style="list-style-type: none"> <li>● American Bureau of Shipping Europe Ltd. (ABS)</li> <li>● French marine classification society (BV)</li> <li>● Det Norske Veritas (DNV)</li> <li>● Germanische Lloyd (GL)</li> <li>● Lloyds Register of Shipping (LRS)</li> <li>● Nippon Kaiji Kyokai (NK)</li> <li>● Polski Rejestr Statkow (PRS)</li> </ul>	Yes Yes Yes Yes Yes Yes No
MTBF	134 y
<b>standards, specifications, approvals / hazardous environments</b>	
standard / for hazardous zone	EN 600079-15 II 3 G EEx nA II T.. KEMA 06 ATEX 0021 X
<ul style="list-style-type: none"> <li>● from CSA and UL</li> </ul>	UL 1604 and UL 2279-15 (Hazardous Location), Class 1 / Division 2 / Group A, B, C, D / T..., Class 1 / Zone 2 / Group IIC / T..
certificate of suitability / CCC / for hazardous zone according to GB standard	Yes
<b>further information / internet-Links</b>	
Internet-Link	
<ul style="list-style-type: none"> <li>● to website: Industrial communication</li> <li>● to website: Industry Mall</li> <li>● to website: Information and Download Center</li> <li>● to website: Image database</li> <li>● to website: CAx-Download-Manager</li> </ul>	<a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a> <a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a> <a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a> <a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a> <a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>

security information

security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

6/30/2021 