## 6GK5108-2BB00-2AB2

**Data sheet** 



SCALANCE XB108-2 unmanaged IE switch, 8x 10/100 Mbit/s Ports, 2x 100 Mbit/s multimode BFOC, for setting up small star and line topologies, LED diagnostics, IP20, redundant power supply 24 V AC/DC Manual available as a download

product type designation	SCALANCE XB108-2
transfer rate	
transfer rate	10 Mbit/s, 100 Mbit/s
interfaces / for communication / integrated	
number of electrical connections	
<ul> <li>for network components or terminal equipment</li> </ul>	8; RJ45
number of 100 Mbit/s ST(BFOC) ports	
<ul> <li>for multimode</li> </ul>	2
interfaces / other	
number of electrical connections	
<ul><li>for power supply</li></ul>	1
supply voltage, current consumption, power loss	
product component / connection for redundant voltage supply	Yes
type of voltage / 1 / of the supply voltage	DC
<ul><li>supply voltage / 1 / rated value</li></ul>	24 V
<ul><li>power loss [W] / 1 / rated value</li></ul>	7.2 W
<ul><li>supply voltage / 1 / rated value</li></ul>	19.2 28.8 V
<ul><li>consumed current / 1 / maximum</li></ul>	0.3 A
product component / 1 / fusing at power supply input	Yes
type of voltage / 2 / of the supply voltage	
supply voltage / 2 / rated value	19.2 28.8 V
ambient conditions	
ambient temperature	
<ul> <li>during operation</li> </ul>	0 60 °C
during storage	-40 +80 °C
during transport	-40 +80 °C
relative humidity	
<ul> <li>at 25 °C / without condensation / during operation / maximum</li> </ul>	95 %
protection class IP	IP20
design, dimensions and weights	
design	compact
width	80 mm
height	117 mm
depth	109 mm
net weight	0.34 kg
fastening method	
<ul> <li>35 mm top hat DIN rail mounting</li> </ul>	Yes

No	
No No	
No No	
No	
ing	
Al.	
No V	
Yes	
A	
No	
product functions / redundancy product function	
Voc	
Yes	
No	
standards, specifications, approvals	
FM3611: Class 1, Divison 2, Group A, B, C, D / T4, CL.1, Zone 2, GP. IIC, T4	
UL 60950-1, CSA C22.2 No. 60950-1	
EN 61000-6-4 (Class B)	
61000-6-2	
71 y	
KF	
KFE	
Yes	
nents	
EN 60079-0:2009, EN60079-15:2010, II 3 G Ex nA IIC T4 Gc, KEMA	
07ATEX0145 X	
Yes; IEC 60079-0, IEC 60079-15, IECEx DEK 14.0025X, Ex nA IIC T4 Gc	
Yes	
1.00	
EN 61000-6-2, EN 61000-6-4	
Yes	
Yes	
103	
http://www.siemens.com/tia-selection-tool	
http://www.siemens.com/simatic-net	
https://mall.industry.siemens.com	
http://www.siemens.com/industry/infocenter	
http://automation.siemens.com/bilddb	
http://www.siemens.com/cax	
https://support.industry.siemens.com	
Siemens provides products and solutions with industrial security	
functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)	

last modified: 11/6/2021 🖸