

NSA 5170C-34EP

Intel® 6th/7th Gen. Xeon®/Core™/Pentium® Processors,
1U Rackmount 32 Switch PoE Ports



Main Features

- 1U compact rackmount size
- Single Intel® 6th/7th Gen. Xeon®/Core™/Pentium® processors
- 4 x DDR4 288-pin DIMM slots, support 1866/2133/2400 ECC, up to 64 GB
- 2 x 2.5" HDD bays with anti-vibration design
- 32 x RJ45 switch port with PoE 15W
- 2 x RJ45 MGMT port
- 1 x RJ 45 console port
- 2 x USB 3.0 port
- 1 x M.2 socket

Product Overview

NEXCOM network appliance NSA 5170C-34EP is based on NSA 5170C extension helps small and medium-sized businesses (SMBs) scrutinize network traffic with ease. Featuring Intel® Xeon® series product family, the NSA 5170C-34EP delivers scalable computing performance, high port density, and easy expansions of high-speed networking interface. By simplifying deployment, configuration, and management of network security controls, NEXCOM network appliance can fend off unauthorized access, patch potential security loopholes, and create protected networks for business environments. The NSA 5170C-34EP provide 32 GbE Ethernet ports with PoE up to 30W (power over Ethernet) can use on IP camera/IP phone or wireless AP, it can more easy to deploy IT infrastructure with few equipment.

Specifications

Main Board

- NSB 5170C (PCH C236)
- Intel® 6th/7th gen. Xeon®/Core™/Pentium® processors

Main Memory

- 4 x 288-pin DDR4 2133/2400 DIMM sockets, up to 64GB ECC

LAN Features

- 32 x GbE RJ45 port from Intel® I350 and Marvell 88E6176
- IEEE 802.3 AF (15.4W), IEEE 802.3 AT (30W) PoE+, total power budget 500W

I/O Interface-Front

- Power status/HDD status/network status/PoE status LEDs
- 1 x Reset button
- 1 x RJ45 type console port
- 2 x USB 2.0 port
- 2 x Management LAN port
- 32 x RJ45 GbE switch port with PoE
- 4 x Antenna hole (reserve)

I/O Interface-Rear

- 1 x Power switch
- 1 x VGA port

Storage Device

- 2 x 2.5" HDD bays with anti-vibration design
- 2 x mini-PCIE slot

Power Input

- ATX 300W single power supply
- ATX 450W redundant power supply
- 500W single PoE power supply

Dimensions

- Chassis dimension: 430 mm x 600 mm x 44 mm

Weight

- Without packing: 12 kg
- With packing: 14 kg

Environment

- Operating temperatures: 0°C~40°C
- Storage temperature: -20°C~75°C
- Relative humidity: 10%~90% non-condensing

Certifications

- CE Approval, FCC Class A, UL

Ordering Information

Barebone

- **NSA 5170C-34EP (P/N: 10S00517004X0)**
6th/7th Gen. Xeon®/Core™/Pentium® processors, 4 x DDR4 memory slots, 2 x 2.5" HDD bays, 2 x mini-PCIE slots, USB ports, VGA port, 32 x GbE RJ45 switch port with PoE and single/redundant ATX PSU

www.nexcom.com



 Mainstream Platform



We reserve the right to change specifications and product descriptions at any time without prior notice.

Last update: 06/25/2019