

Main Features

- Support Intel® Atom™ Dual Core D525 Processor
- Support DDR3 SO-DIMM SDRAM, up to 2GB
- Support VGA/LVDS 18/24-bit Display
- Dual Intel® Gigabit Ethernet
- Support PCI-104, 1 x Mini-PCI Express Socket
- 4 x COMs, 6 x USB2.0
- Single DC12V Power Input

Product Overview

The EBC 352 is a 3.5" ECX board with an on-board Intel® Atom™ dual core D525 with L2 cache 1MB and supports DDR3 SO-DIMM SDRAM module. It features dual display application to support independent CRT and LVDS 18/24-bit interface, dual Gigabit Ethernet, one PCI-104 and one Mini PCI Express slot.

Specifications

CPU Support

- Onboard Intel® Atom™ Dual Core D525 (1.8GHz, 1M Cache) processor

Main Memory

- 1 x 204-pin DDR3 SO-DIMM socket, DDR3 800 2GB Max., Non-ECC and Un-buffered

Chipset

- Intel® NH82801HBM (ICH8M)

BIOS

- AMI BIOS
- Plug & Play support
- Advanced Power Management
- Advanced Configuration & Power Interface
- 8M bits SPI ROM

On-board LAN

- 2 x Intel® GbE LAN controllers
- Support Boot From LAN (PXE) and Wake on LAN (WoL)
- 2 x RJ45 with LED

Display

- Intel® D425/D525 integrated graphic engine, support Directx*9, with Intel® Clear Video Technology on MPEG2 Hardware Acceleration
- Analog VGA interface: 1 x DB15 VGA port, support up to 2048 x 1563@ 60Hz resolution
- 2 x DF-13 20-pin LVDS connector, support single (24-bit) or dual (48-bit) LVDS panel support
- CCFL interface: 1 x 7-pin JST connector, 5V or 12V power source to enable LCD Panel backlight Inverter

Audio

- Realtek ALC888 CODEC for High Definition
- 1 x Mic-in and 1 x Line-out Pin header

Expansion

- 1 x Mini-PCIe socket
- 1 x PCI-104 slot

I/O Interface

- Serial port: 4 port
 - 1 x RS232 DB9 Connector
 - 2 x RS232 with 10-pin box header, 2.0mm pitch
 - 1 x RS232/422/485 (COM2) with 10-pin box header, 2.0mm pitch
- USB2.0: 6 ports
 - 2 ports with USB2.0 connector
 - 4 ports with internal JST connector
- 8 x GPIO, 10-pin pin header, (GPI 0~3 and GPO0~3) with TTL Level (0/5V)
- On-board Power LED and HDD Active LED Pin Header
- 1 x 3-pin fan connector (for CPU)
- 1 x Keyboard/Mouse pin header
- On board Buzzer/SMBus2.0/Reset SW


Watchdog Timer

- Watchdog timeout can be programmable by Software from 1 second to 255 seconds and from 1 minute to 255 minutes (Tolerance 15% under room temperature 25°C)

Storage

- 2 x SATA connector (support 2.5" HDD and SATA DOM)

Block Diagram



- 1 x CF socket

System Monitor

- Monitoring of 4 voltages and 2 temperatures
- 4 voltage (Vcore, +12V, +3.3V, +5V)
- 2 temperatures (CPU, system)

On-board RTC

- On-chip RTC with battery backup
- 1 x External Li-Ion battery

Power Input

- Support AT and ATX mode (ATX as the default)

Power Requirements

- Power requirement: +12VDC Input
- One 4-pin power connector

Dimensions

- 3.5" ECX form factor
- 146mm (L) x 105mm (W) (5.7" x 4.1")

Environment

- Operating temperatures: 0°C to 60°C
- Storage temperature: -20°C to 85°C
- Relative humidity: Operating 10% to 90%, non-condensing

Certifications

- CE approval
- FCC Class A

Ordering Information

- **EBC 352 (P/N: 10E00035200X0) RoHS Compliant**
Low power Embedded Board with Intel® Atom™ Dual Core D525 processor support DDR3 SO-DIMM memory module