

DSS-100



Main Features

- PowerDigiS Digital Signage system
- Seamless hardware and software integration for operation reliability
- Flexible display configuration
- Presentation content support is rich and versatile
- Self-contained device for easy deployment

Product Overview

Digital Signage Solution starter kit includes PDSB 325 with preloaded PowerDigiS signage software. PowerDigiS is targeting for entry-level digital signage applications. PDSB 325 is enclosed in a compact chassis with low power consumption and can be easily integrated to display such as LCD TV or PDP at site installation. It works perfect for increasing digital signage applications within retail outlets, department stores, entertainment venues, restaurants, hotels, bus/train stations, schools/universities and hospitals for dynamic message, delivering, advertising, or brand promotion.

Specifications

PC System (PDSB 325)

- PowerDigiS Digital Signage player

I/O Interface

- 1 x 19V DC in
- 2 x USB2.0
- 4 x USB 3.0
- 1 x DB9 for RS-232
- 1 x VGA
- 1 x HDMI (4K Resolution)
- 1 x RJ45 with LEDs for 10/100/1000Mbps Ethernet
- 1 x Mic-in/1x Line-out

Signage Display

- 10.4" TFT LCD Monitor
- Resolution 800 x 600
- Brightness 300 nits

Dimensions

- 480mm (L) x 340mm (W) x 140mm (D)

Weight

- 8Kg

Ordering Information

- **DSS-100**
Digital Signage Solution
PDSB 325, PowerDigiS signage software

Block Diagram

