



Main Features

- ♦ OnBoard Intel® Atom™ D425 Processor, 1.8GHz
- ♦ Intel® ICH8M chipsets
- ♦ Dual Intel® GbE LAN ports Support WoL, Teaming, PXE
- ♦ 4 x USB 2.0
- ♦ 1 x RS232/422/485 and 3 x RS232
- ♦ 1 x Mini-Pcie with Two Antenna Holes and One SIM Card Holder
- ♦ 1 x DB15 Digital Input & Output
- ♦ Support +12VDC Input; Support ATX power mode

Product Overview

Designed with Intel® D425 1.8GHz processor and ICH8M embedded chipset and 12VDC input to take a low power consumption advantage, NISE 103 is a compact fanless industrial computing housed in a size of 185mm x 131mm x 54mm. The NISE 103 supports three RS232, one RS232/422/485, two GbE LAN ports, four USB ports, one digital I/O, one VGA display, audio jack (speaker-out, Mic-in) and one external CF card socket. It is also a wireless-ready platform which has Mini-Pcie socket and SIM card holder onBoard to support optional GSM wireless module or Wi-Fi module (default). EZ Controller, NISE 103 has a digital I/O port which offers 8X isolated digital input/output channels.

With isolation protection of 2,500VDC, and dry contact support, NISE 103 can be applied to industrial and building automation applications. With rich I/O connection in palm-sized system, NISE 103 is an ideal fanless system for gate control, public information, self-service system, POS, Kiosk, low-power budget devices, and transportation applications etc.

Specifications

CPU Support

- ♦ OnBoard Intel® Atom™ D425 processor, 1.8GHz
- ♦ Intel® ICH8M chipsets

Main Memory

- ♦ 1 x DDR3 SO-DIMM sockets, single channel, support up to 2GB DDR3 667/800 SDRAM, un-buffered and non-ECC

I/O Interface-Front

- ♦ ATX power on/off switch
- ♦ HDD access/power status LEDs
- ♦ 3 x COM ports
COM2: RS232/422/485
COM3& COM4: RS232
- ♦ 2 x USB 2.0 port
- ♦ Audio jack (Line-out, Mic-in)
- ♦ 2 x Antenna holes

I/O Interface-Rear

- ♦ 1 x VGA
- ♦ COM1: 1 x RS232
- ♦ 2 x Intel® GbE LAN port; Support WoL, Teaming and PXE
- ♦ 2 x USB 2.0 port

- ♦ +12VDC power input
- ♦ 1 x DB15 male digital input & output


Digital Input & Output

- ♦ 4 x Digital Input (Source type)
 - Input Voltage (Dry Contact):
Logic 0: Close to GND
Logic 1: Open
 - Input Voltage:
Logic 0: 3V max
Logic 1: +5V to +30V
- ♦ 4 x Digital Output
 - Supply voltage: 5 ~ 30VDC
 - Sink current: 200 mA max. per channel

Device

- ♦ 1 x 2.5" HDD driver bay
- ♦ 1 x External CF Socket
- ♦ 1 x SATA DOM
- ♦ 1 x Mini-Pcie socket
 - Default: support optional Wi-Fi module
 - Option: support optional 3.5G module

Dimension Drawing



Power Requirements

- ♦ DC to DC power designed for onBoard support of +12VDC
- ♦ 1 x optional 12V, 60W power adapter

Dimensions

- ♦ 185mm (W) x 131mm (D) x 54mm (H) (7.28" x 5.2" x 2.13")

Construction

- ♦ Aluminum chassis with fanless design

Environment

- ♦ Operating temperature:
Ambient with air flow: -5°C to 55°C
(According to IEC60068-2-1, IEC60068-2-2, IEC60068-2-14)
- ♦ Storage temperature: -20°C to 80°C
- ♦ Relative humidity: 10% to 93% (non-Condensing)
- ♦ Shock protection:
 - HDD: 20G, half sine, 11ms, IEC60068-2-27
 - CF: 50G, half sine, 11ms, IEC60068-2-27
- ♦ Vibration protection w/ HDD Condition
 - Random: 0.5Grms @ 5 ~ 500Hz according to IEC60068-2-64
 - Sinusoidal: 0.5Grms @ 5 ~ 500Hz according to IEC60068-2-6

Certifications

- ♦ CE approval
- ♦ FCC Class A

OS Support List

- ♦ Windows XP 32bits
- ♦ Windows 7 32bits
- ♦ WinCE 6.0

Ordering Information

Barebone

- ♦ **NISE 103 (P/N: 10J00010300X0)**
Intel® Atom™ D425 Fanless System
- ♦ **NISE 103D (P/N: 10J00010302X2)**
Intel® Atom™ D525 Fanless System
- ♦ **12V, 60W AC/DC power adapter w/o power cord (P/N: 7400060018X00)**