

FTA 5180

1U Rackmount nexCPE™ Appliance w/ Intel® Xeon® D-1700 Processor, 6 x 10G SFP+, 2 x 10G RJ45, 2 x 2.5G RJ45 Ports, and 1 x LAN Module Slot

NEXCPE™



Main Features

- Intel® Xeon® D-1734NT processor
- 4 x RDIMM/UDIMM socket, support ECC/non ECC, up to 256GB
- 2 x M.2 2242 Key M with SATA signal
- 6 x 10G SFP+ ports
- 2 x 10GBaseT RJ45 PoE++ port
- 2 x 2.5G RJ45 PoE++ ports
- 1 x LAN module slot
- Supports IPMI2.0
- Supports Intel® QAT
- TPM2.0 onboard

Product Overview

FTA 5180 is a high-end networking appliance in 1U rackmount form factor for edge computing applications. With Intel® Xeon® D-1700 LCC processor inside, it provides impeccable performance and enables 10 high-bandwidth interfaces for speedy connections, including 6 x 10GbE SFP+ and 2 x 10GbE & 2 x 2.5GbE RJ45 PoE++ ports. FTA 5180 features BMC and out-of-band (OOB) remote management. It also supports 5G (sub-6 GHz) and Wi-Fi modules installation, offering extra FWA capability and connecting a variety of devices seamlessly.

Specifications

Main Board

- Intel® Xeon® D-1734NT, SoC, BGA type, 8 cores, w/QAT
- TPM2.0 onboard
- Dual BIOS onboard

Main Memory

- 4 x DDR4 2666 RDIMM/UDIMM ECC/non ECC sockets, up to 256GB

Storage

- 2 x M.2 2242 Key M SATA SSD

Interface External

- Button: PWR/reset
- LED: PWR/SSD/SYS1/SYS2/PoE
- 8 x SMA connectors
- 2 x USB 3.0 ports
- 1 x RJ45 console port
- 1 x RJ45 management port
- 6 x 10G SFP+ ports
- 2 x 10GBaseT RJ45 PoE++ ports
- 2 x 2.5G RJ45 PoE++ ports
- 1 x VGA port
- 1 x LAN module slot

- 2 x AC power inlets
- 4 x Smart fans

Interface Internal

- 1 x M.2 3042 Key B slot for 5G module
- 1 x mini-PCIe slot for Wi-Fi module

Power

- 650W (1+1) redundant PSU

Dimension and Weight

- Chassis dimension (mm): 438 x 370 x 44mm (W x D x H)

Environment

- Operating temperature: 0°C~40°C
- Storage temperature: -20°C~80°C
- Relative humidity: 10%~90% non-condensing

Environment

- Operating temperatures: 0°C~40°C
- Storage temperature: -20°C~75°C
- Relative humidity: 10%~90% non-condensing

Certification

- CE/FCC class A
- CE-LVD

Ordering Information

- **FTA 5180 (P/N: 10FT0518000X0)**
1U rackmount nexCPE™ appliance w/ Intel® Xeon® D-1734NT processor, 6 x 10G SFP+, 2 x 10G RJ45, 2 x 2.5G RJ45 ports, and 1 x LAN module slot