HEB

ALUMINIUM WEATHERPROOF CAMERA HOUSING



IP66

IP67





HEB + WBOVA2

DESCRIPTION

Robust and large aluminium housing designed to fit combinations of 1/2", 1/3" and 1/4"cameras, with different types of optics

The frontal opening system allows an easy access to the camera and all internal connections.

A wide range of accessories for mounting the equipment is available thereby satisfying all installation needs.

MAIN FEATURES

IP66/IP67 (with cable glands or optional sealing rings)

Slide-extractable body with hinged system

Pre-arranged for internal cable management bracket

Available accessories: heater, camera power supply, blower and air filter

| TECHNICAL DATA |
|---|
| GENERAL |
| Aluminium back and front cover plates |
| Extruded aluminium body, external slide and sunshield |
| Epoxypolyester powder painting, RAL9002 colour |
| Stainless steel external screws |
| MECHANICAL |
| Cable glands: 3xM16 |
| Glass window extra clear |
| Dimensions (WxH): 90x81mm (3.5x3.2in) |
| Internal usable area (WxH): 90x85mm (3.5x3.3in) |

ELECTRICAL

Unit weight: 3.2kg (7.1lb)

Heater (Ton 15°C±3°C (59°F ±5°F), Toff 22°C±3°C (72°F±5°F))

Internal usable length (without accessories): 320mm (12.6in) Internal usable length (with accessories): 250mm (9.8in)

- Power supply/Consumption: IN 12Vdc/24Vac, 20W max
- Power supply/Consumption: IN 120/230Vac, 40W max

Blower with thermostat and air filter, Ton 35°C±3°C (95°F±5°F) Toff 20°C±3°C (71°F±5°F) and back cover

- IN 12Vdc, consumption 4W max
- IN 24Vac, consumption 4W max
- IN 230Vac, consumption 4W max, complete with voltage transformer

Camera power supply

- IN 100-240Vac, 50/60Hz OUT 12Vdc, 1.25A
- IN 230Vac, 50Hz OUT 24Vac, 50Hz, 400mA

ENVIRONMENT

For installation indoors and outdoors

Operating temperature with heater: from -20°C (-4°F) up to +60°C (140°F) Salty fog resistance, to 1000 hours (ISO9227)

CERTIFICATIONS

CE EN61000-6-3, EN60065, EN50130-4

IP66/IP67 EN60529 with cable glands

IP66/IP67 EN60529 with special gaskets and bracket with internal cable channel
IP55 EN60529 with bracket with internal cable channel

| ACCESSORIES | |
|-------------|---|
| ACCESSORIES | |
| OHEH01B | Heater 12Vdc/24Vac for HEB, HEK housings |
| OHEH02B | Heater 120/230Vac for HEB, HEK housings |
| OHEBVF1 | Blower with thermostat and air filter IN 12Vdc, for HEB housing, not compatible with WB0VA2 and WB0V3A2 brackets |
| OHEBVF2 | Blower with thermostat and air filter IN 24Vac, for HEB housing, not compatible with WB0VA2 and WB0V3A2 brackets |
| OHEBVF3 | Blower with thermostat and air filter IN 230Vac, for HEB housing, not compatible with WB0VA2 and WB0V3A2 brackets |
| OHEPS01B | Wide range camera power supply IN 100-240Vac - OUT 12Vdc, 1.25A, for HEB housing |
| OHEPS02B | Camera power supply IN 230Vac - OUT 24Vac, 10VA, for HEB housing |
| OWBIP2 | Sealing rings kit (3xM16) IP66/IP67 for WBOVA2 and WCM4A2 brackets for PUNTO, HOV, HTV, HTC, VERSO, VERSO POLAR, VERSO COMPACT, HEB, HEK housings |
| OSUPPIR | Support for 1 GEKO IRH illuminator under the housing (Not compatible with WBOVA2 wall bracket) |
| OHEGBB | Weatherproof junction box |

RELATED PRODUCTS

PTH300 Horizontal/vertical Pan & Tilt

| BRACKETS AND ADAPTORS | | | | |
|-----------------------|--|--|--|--|
| WBJA | Wall mount bracket | | | |
| WBMA | Wall bracket with ball joint | | | |
| WB0VA2 | Wall bracket with internal cable channel | | | |
| WB0V3A2 | Wall bracket with internal cable channel, counterplate and support box, not compatible with OHEBVF1, OHEBVF2 and OHEBVF3 | | | |
| WCM3A | Ceiling bracket with ball joint | | | |
| WCM5A | Ceiling bracket with ball joint | | | |
| WCM4A2 | Ceiling bracket with internal cable channel | | | |
| WFWCA | Column bracket with joint | | | |

| SPARE PARTS | |
|-------------|--|
| OHEBS32A000 | Sunshield HEB32 |
| DOTHE01 | Spacers for camera and lens |
| OHEBMAN | Cable glands, gaskets and screws |
| OHBCFA04 | Front cover with glass, screws and gaskets |
| OHBFP04B | Back cover with cable glands, gaskets and screws |

| PACKAGE | | | |
|--------------|---------------|---------------------------------|---------------|
| Model Number | Weight | Dimensions (WxHxL) | Master carton |
| HEB32K1A000B | 3.5kg (7.7lb) | 16.5x15.5x49cm (6.5x6.1x19.3in) | 10 |

| AVAILABLE MODELS | | | | | | | |
|------------------|-----------|----------------------|--------------------|-----------------|--|--|--|
| Model Number | Sunshield | Heater 120Vac/230Vac | Heater 12Vdc/24Vac | Max consumption | | | |
| HEB32K1A000B | 1 | 1 | _ | 40W | | | |
| HEB32K2A000B | 1 | - | 1 | 20W | | | |
| HEB32K0A000B | 1 | - | - | - | | | |

TECHNICAL DRAWINGS

The dimensions of the drawings are in millimetres.

